

Endurance Heavy-Duty Pipeline Identification Tape

Proven, durable Endurance Identification Tape for extreme conditions

The performance of identification tape is dependent on the quality of the materials used in its manufacture.

Silver Fox has focused on creating the most long-lasting and best performing tape, for maximum legibility and adhesion in the most demanding environments.

Silver Fox ID tape is made from 100% polyester substrate and laminate using the best adhesives in the world. Our heavy duty tape has been independently tested in the harshest conditions – namely SAEJ 1960, an accelerated ageing test that exposes the product to a number of different elements including specially tuned UV light. The test was Carried out for 2,500 hours which represents a simulated accelerated ageing for up to 10 -12 years in Northern European climates. It is this dedication to the highest standards that has brought leading energy companies to Silver Fox for their specific solutions. Our tape is used currently on energy installations around the world such as the North Sea, Gulf of Mexico, West Africa and the Caspian Sea.

All tapes are not the same so let our experience guide you. Call us for advice for your specific requirements, including color, text and symbols. We maintain a huge library of previously supplied messages.

Our one part tape is quick to apply. It is used to identify the contents and flow of service pipes used on oil platforms and process plants generally.

While our Endurance Tape has been specifically designed for external use, it can equally be used internally for additional peace of mind.



Key Benefits

- ✓ Exceptional UV and salt-water resistance, including excellent resistance to a wide range of chemicals and solvents
- ✓ Manufactured to your exact requirements of color, text and symbols
- ✓ Service temperature range from -40°C to +120°C
- ✓ Independently tested to SAEJ 1960 (non-destructive test) standard for approximately 10-12 years simulated weathering in Northern European conditions
- ✓ Backed with a release liner so you can cut the amount you require, this means that in areas of limited access you don't have to wind the roll around the pipe
- ✓ Available with any text (in any language), BS 5252 color or combination of colors and directional arrows
- ✓ Lengths available 25 or 50 metres

SILVER FOX

Make Labeling your Signature for Quality and Reliability



Visit our website at www.pipe-marking.com
or contact us direct on +44 (0) 1707 37 37 27
e-mail sales@pipe-marking.com
to discuss your requirements

Endurance Heavy-Duty Pipeline Identification Tape

Base Material	White Polyester with a siliconised kraft backing paper
Surface Finish	Ultra-violet stabilised transparent film
Adhesive	High strength acrylic adhesive. High initial adhesion to plastics, metals and painted surfaces. Resists flagging and edge lifting
Service Temperature Range	-40°c to +120°c
Testing	SAE J 1960 <i>Simulated Northern European Weathering</i> MIL-STD-202G (Method 106G) <i>Moisture Resistance</i> MIL-STD-810F (Method 502.4) <i>Storage (Low Temperature) -25°c</i> IEC60068-2-52 <i>Test kb Salt Mist (Cyclic)</i> H ₂ S (Hydrogen Sulphide) Sour Ageing

Visit our website at www.pipe-marking.com
or contact us direct on +44 (0) 1707 37 37 27
e-mail sales@pipe-marking.com
to discuss your requirements

TECHNICAL
DATA
ORDER
CODES

Information contained in this product data sheet is based on data we believe to be reliable. The typical values listed are not for use in specifications. They are given for information only and without guarantee and do not constitute a warranty. The purchaser should independently determine prior to use the suitability of this product for their specific purpose.

