

STARGUARD



WALL MOUNTING BRACKET



POLE TOP MOUNTING BRACKET

Options

DESCRIPTION	SUFFIX
Photocell	PC




e.g. STG 10912PC etc

Spares

DESCRIPTION	NUMBER
Cover glass	STG 11275
GES porcelain skirted lampholder	LH 5034

Photometric Data

250W SON-T 28000lm 8 metre high



STARGUARD

ZERO upward light, low glare area floodlight

Classified IP65  CE

- ZERO upward light - eliminates sky glow
- High elevation peak beam angle for outstanding area coverage relative to mounting height
- High beam efficiency with low glare
- Corrosion-resistant and fire-retardant GRP moulded body - light grey finish
- Clear toughened/safety glass cover
- Aluminium heat sink ensures cool running of control gear for optimum life in high ambient temperatures
- Pole top or wall mounted versions
- Photocell option available
- Supplied complete with lamp



Range

LAMP	MANUFACTURER	WALL MOUNTED NUMBER	kg	POLE TOP NUMBER	kg
High pressure sodium lamps					
150W SON-T	Any	STG 10912	10.3	STG 11000	10.5
250W SON-T	Any	STG 10913	10.8	STG 11001	11.0
Metal halide lamps - compatible with high pressure sodium control gear					
150W MBI-T	Any ●	STG 10909	10.3	STG 10997	10.5
250W MBI-T	Any ●	STG 10910	10.8	STG 10998	11.0
Metal halide lamps - compatible with mercury (MBF) control gear and semi-parallel ignitor					
250W MBI-T	Any ▲	STG 10911	10.1	STG 10999	10.3

SUPPLIED LAMPS: ● Venture Whitelux. ▲ Philips HPIT Plus.

IMPORTANT: SON(-T) LAMPS WITH INTERNAL STARTERS ARE NOT RECOMMENDED.

